

BenQ Digital Projector

MX760/761



(for reference only)



HIGHLIGHTS

- Microphone in with two 10W Speakers
- USB Reader
- USB Display (Plug-n-Play)
- LAN Display
- 4-1 Display
- Remote Desktop
- Wireless Display (Optional)
- Filter Free Design
- No Color Decay
- Crestron RoomView Compatible
- PJ-Link Compatible
- 3700/4200 ANSI Lumens
- XGA Native Resolution
- BrilliantColor™
- 3D Color Management
- VIDI™
- Auto Keystone (Vertical)
- Keystone ± 40 Degree
- 6 Segment Color Wheel
- Variable Audio Out
- Closed Captioning

Projection System	DLP® technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	3700/4200 ANSI lumens	
Contrast Ratio	5300:1 (Full on/Full off)	
Keystone	Auto Keystone Vertical ± 40 Degree; Manual Vertical ± 40 Degree	
Aspect Ratio	4:3 Native (5 aspect ratio selectable)	
Color	Full 16.7 million color palette	
Lens	F=2.45~3.07 Lens Shift	
Zoom Ratio	Manual Zoom, 1.6:1	
Image Size (Diagonal)	18" to 300"	
Throw Ratio	1.4 to 2.24 (70" @2M)	
Lamp	300W, 2000/3000 hours (Normal/Economic mode)	
Computer	VGA(640 x 480) to UXGA (1600x1200)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-99 kHz	
Vertical Scan Rate	48-120 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 2 LAN Networking: RJ-45 x 1 (LAN Display) USB connector: Type A x 1, Type Mini-B x 1 (USB Display) HDMI (v1.3) x 1
	A/V	S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 Microphone: Stereo Mini Jack x 1 Audio L/R : RCA x 1 Stereo Mini Jack x 1
Output Terminals	PC	D-sub 15 pin x 1
	Audio	Variable Audio Out : Stereo Mini Jack x 1 Speaker: 10W x 2
Control Terminal	Serial Connector : RS232 9 pin x 1	
	RJ45 x 1 (LAN Control) USB connector: Type A x 1 (for JPEG Reader), Type Mini-B x 1	
Dimensions(W x H x Weight)	11.4 x 5.03 x 9.9 inch (290 x 128 x 252 mm) 7.26 lbs (3.3 kg)	
Power Supply	100 to 240 VAC, 50/60 Hz	
Power Consumption	419W, Standby < 1W	
Audible Noise	36/31 dB (Normal/Economic mode)	
On-Screen Display Languages	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Indonesian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (26 Languages)	
Picture Modes	PC Input:	A/V Input :
	Dynamic Mode	Dynamic Mode
	Presentation Mode	Presentation Mode
	sRGB Mode	sRGB Mode
	Cinema Mode	Cinema Mode
	User 1 Mode	User 1 Mode
Functions	User 2 Mode	User 2 Mode
	BrilliantColor™	Blank
	VIDI™	Panel Key Lock
	3D Color Management	Auto Off
	Crestron LAN Control	Security Password
	Closed Captioning	HDTV compatible
	Digital Zoom (x2)	High Altitude Mode
	Variable Audio Out	"Q?" Hot Key for FAQ
	Quick Cooling	3D Ready
	Quick Auto Search	Freeze
	Closed Captioning	Quick Auto Search
	Quick Cooling	PJLink Compatible
	Quick Start Guide	VGA(D-sub) cable
	Accessories (Standard)	Manual CD
Remote Control w/battery		Soft Carry Case
Presentation Plus		Spare Lamp Kit
Accessories (Optional)	RS232 Cable	