

ED-X24

INNOVATE
The Future of Projection



EDUCATION LCD PROJECTOR

Make the most of your lessons with the affordable ED-X24. Built with the exacting standards you've come to expect from Hitachi, this versatile projector can be used in a variety of settings, fitting perfectly into any classroom.



- XGA resolution
- 1500 ANSI Lumens
- Long lamp life - 6000 hours (Eco Mode)*
- Extended filter cleaning cycle - 1000 hours
- Quick ON and Instant OFF
- Low noise level - 29dB in Whisper Mode
- Blackboard and Whiteboard Modes
- Input Source Naming
- My Button
- Anti Theft features:
 - PIN-Lock
 - MyScreen PIN-Lock
 - Keypad Lock
 - Kensington Lock



www.hitachidigitalmedia.com

HITACHI
Inspire the Next

ED-X24 Technical specifications



Screen Size (Diagonal)	Projection Distance (a)		Screen Height (cm)	
	min. (m)	max. (m)	b (top)	c (bottom)
30" (0.8)	0.8	1.0	38	8
40" (1.0)	1.1	1.4	51	10
50" (1.3)	1.4	1.7	64	13
60" (1.5)	1.7	2.1	76	15
100" (2.5)	2.9	3.5	127	25
150" (3.8)	4.4	5.2	191	38
200" (5.1)	5.8	7.0	254	51
250" (6.4)	7.3	8.8	318	64
300" (7.6)	8.8	10.5	381	76



HITACHI DIGITAL MEDIA, Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road, Maidenhead, Berkshire SL6 8YA UNITED KINGDOM
Tel: +44 (0)1628 585 000 Fax: +44 (0)1628 585 500 www.hitachidigitalmedia.com

*The stated lamp life refers to the average life expected in ideal operating conditions with usage in accordance with the manual. The majority of, but not all lamps should achieve this figure. The specification above and photography is for reference only and may be subject to change.

OPTICAL

LCD Panel		0.63" P-Si TFT x 3
Resolution		XGA
Brightness	Bright Mode	2200 ANSI Lumens
	Normal Mode	1500 ANSI Lumens
Contrast ratio		400:1
Lens		Manual focus, manual zoom x 1.2
Lamp wattage		190W UHP
Lamp life		3000 hours (Normal Mode)/6000 hours (Eco Mode)*
Diagonal display size		30~300" (60"@1.7m, Wide)
Number of colours		8 Bit/colour, 16.7M colours
Keystone		5:1 upward shift, fixed

COMPATIBILITY

Computer compatibility	IBM Compatible VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, MAC 16"
Video compatibility	NTSC/PAL/SECAM/PAL-M/PAL-N/NTSC4.43/PAL60 SDTV: 480i, 480p, 576i, 576p HDTV: 720p (@50/60Hz), 1080i (@50/60Hz), 1125p (1080p@50/60) DDC2B
Plug & Play	

FEATURES

Speakers	1W mono
Basic functions	Freeze, Magnify, Blank, Auto adjustment, Search
Picture adjustments	Equalizing gamma correction, 2-3 Pull Down, Progressive Scan, Video noise reduction
Digital keystone	Manual vertical keystone ±30 degrees (@ XGA 60Hz)
Advanced features	MyScreen, My Memory, My Button, My Text, My Source, Blackboard/whiteboard mode, Daytime mode, Input source naming (English), Resolution setting, Template, Closed caption (for NTSC only), Audio pass through
Outward	Easy lamp replace from top, Air filter sliding from bottom to front
Power on & off	Quick ON, Direct On, Auto Off
Security systems	PIN-Lock, MyScreen PIN-Lock, Keypad Lock, Kensington Lock, My Text Lock, Security bar, Serial number label on side
OSD languages	MENU: 31 Languages OSD: English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabic, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil)

CONNECTIONS

Computer input	1 x 15-pin Mini D-sub (shared with Component Video)
Computer output	1 x 15-pin Mini D-sub
Video input	1 x RCA Jack
	1 x S-Video Jack
Audio input	1 x Stereo Mini Jack (selectable on OSD)
Audio output	1 x Stereo Mini Jack

POWER

Power supply	100-120V/220-240V, auto switching
Power Consumption/Standby	330W/<5W

PHYSICAL

Dimensions (W x H x D)	317 x 98 x 288mm (excluding feet and extrusions)
Weight	3.2Kg
Noise level	29dB (Eco Mode)/35dB (Normal Mode)
Air filter	Urethane (1000 hour filter cleaning cycle in Eco Mode)

MISCELLANEOUS

Lamp indicator light, Power light, Ceiling mount image, Rear projection image

CERTIFICATION

UL60950/C-UL, FCC Part 15 Class B, CE, AS/NZS CISPR22 Class B

ACCESSORIES SUPPLIED

Remote control with batteries, Computer cable, Power cord, User manual (detail & concise)

OPTIONAL ACCESSORIES

Replacement lamp	DT01022
------------------	---------

WARRANTY

Projector warranty	3 Years
Lamp warranty	3 Years

Image Size 16:9

Screen Size (Diagonal)	Projection Distance (a)		Screen Height (cm)	
	min. (m)	max. (m)	b (top)	c (bottom)
30" (0.8)	0.9	1.1	35	2
40" (1.0)	1.2	1.5	47	3
50" (1.3)	1.6	1.9	59	3
60" (1.5)	1.9	2.3	71	4
100" (2.5)	3.2	3.8	118	7
150" (3.8)	4.8	5.7	176	10
200" (5.1)	6.4	7.6	235	14
250" (6.4)	8.0	9.6	294	17
300" (7.6)	9.5	11.5	353	21

